

Closing (T)	2000	Fast closing (m/min)	30
Opening (T) brut	107 (427cm ²)	Work closing (mm/s)	1 à 30
Opening (T) max	400	Opening slow (mm/s)	2 à 16
Réaction parallèle (T) max	400	Opening fasr (m/min)	30
Réaction parallèle (T/bar)	3.2		
Stroke cylinder parallèle(mm)	150		
Diamètre cylinder parallèle(mm)	320	Ejection Hydraulic (bar)	200
Pressure by cylinder parallèle(bar)	155		
Sise platen (m)	3 × 2,5	Work Pressiure (bar)	267
Weight max mold (T)	50	Power instal (KW)	130
Weight max mold platen mobil(T)	25		
Heating	Huile	Pressure auxiliary (bar)	200
Number heating Zone	8	Flow auxiliary (L/min)	60
		Nb Auxiliary fix platen	3+EJ
Opening maximum(m)	3	Nb Auxiliary fix mobil	3+EJ
Stoke platen mobil(m)	2		
Dead light (*1)	1		
Size between the column	3		

Type Block	Sistema
nb et Force block	K160R
	1 x 70 T
group hydraulic	
Nb motor et power	2x55 kw
Type pump	QT54-063R
Flow fix/variable	Fixe
Volume oil Accumulatr	250 L
Volume Azote	V0=620L
Pressure Initiale P0	250
Pressure min P1	265
Pressure Max P2	315

