

NTY3-150 with FANUC 31i-B control		1 SET
- INCLUDING -		
Left spindle bar capacity	51mm / 5,000min-1 / A2-5	0 SET
Left spindle motor	FANUC AC 15/11 kW	1 SET
Left spindle C-axis control	including brake	1 SET
Right spindle bar capacity	51mm / 5,000min-1 / A2-5	1 SET
Right spindle motor	FANUC AC 11/7.5kW	1 SET
Right spindle C-axis control	including brake	1 SET
Dodecagonal drum turret	Max 24stations	U:L&R / L:L
Milling function	12st / FANUC5.5/3.7kW / 6,000min-1	U:L&R / L:L
UPPER Y-axis	'+45 / -45 mm	U:L&R
LOWER Y-axis	'+35 / -35 mm	LOWER
19" color LCD	Smart-X	1 SET
Luck-bei II	NT manual guide I	1 SET
Y-axis unit for upper turret		upper
NT nurse 2		1 SET
NT Work Navigator	Torque type	1 SET
Part program storage length	1,200m (3-turrets total)	0 SET
Number of registerable programs	1,000programs (3-turrets total)	0 SET
Tool offset memory	99 pairs	1 SET
Helical interpolation		1 SET
Spindle speed override switch		L/R
Collision guard		1 SET
CE marking		1 SET
Bar feeder interface	LNS	1 SET
8MB part program storage size	20480 m of Part program storage length (Total) 4000 pcs of Number of registered programs (Total)	1 SET
Polygon cutting function		1 SET
Program restart		1 SET
Automatic tool offset		1 SET
Hobbing function		1 SET
Left spindle 65MM bar capacity	φ65/A2-6/4300MIN-1	1 SET
Fixed air blow		L
Fixed air blow		R
Coolant piping at upper side of spindle		L
Coolant piping at upper side of spindle		R
Air & Coolant blow through spindle	for bar capacity 51mm	R
Air & Coolant blow through turret for L-Upper turret		1 SET
Air & Coolant blow through turret for R-Upper turret		1 SET
Air & Coolant blow through Lower turret		1 SET
Preparation for BRINKMANN coolant pump TH416/A390 retro fit		1 SET
Coolant level float switch		1 SET
Non return valve for coolant supply	3pcs/set	1 SET
Chip conveyor	Right side outlet	1 SET
Part catcher type T / bucket on turret with stocl	DIA 65mm x L150mm / 1.5kg	1 SET
Part ejector cylinder type	Cylinder stroke 100mm	1 SET
2-step (high/low) change of chucking pressure for Left spindle		1 SET
2-step (high/low) change of chucking pressure for Right spindle		1 SET
Software preparation for Manual detachable tool setter		1 SET
Quick skip function interface		1 SET
Triple alarm light (Yellow, Red and Green)		1 SET
Automatic power off		1 SET
Automatic door		1 SET
Preparation hole for oil mist collector retro-fit	100mm	1 SET
Additional M-code TYPE C	8 pairs	1 SET
Spindle speed fluctuation detection / G25,G26		1 SET
Sequence number collation stop		1 SET
3rd/4th reference position return		1 SET
Manual handle retrace		