

12K-40T-IN

Spindle: 12,000-rpm Spindle, 40 taper, 30 hp (22.4 kW) vector drive, inline direct-drive; requires balanced toolholders with G2.5 rating above 10,000 rpm

Included

1GB

Control Options: Standard Program Memory; 1 GB of onboard memory for program storage and backup.

Included

55GAL

Coolant Tank: 55-Gallon (208 liter) Coolant Tank with 3/4 hp (0.6 kW) pump; flows 5.25 gpm @ 30 psi (19.9 L/min @ 2 bar), and features a multi-section labyrinth design that prevents chips from reaching the coolant pump.

Included

AUTO DOOR-MILL

Options: Auto Door for Mills; opens and closes the machine doors automatically via M-code, or manually via a switch.

Included

EPFDM

Control Options: Early Power-Failure Detection Module; senses a power failure or severe drop in incoming line voltage and quickly brings all axis motion to a safe and controlled stop.

Included

ETHERNET

Control Options: Ethernet Interface; allows you to easily transfer files to and from the machine over a local wired network.

Included

HAAS CONNECT

Control Options: HaasConnect: Remote monitoring of your Haas machine. Requires the machine to be connected to the Internet.

Included

HAASDROP

Control Options: HaasDrop Wireless File Transfer is a fast and convenient method for sending images, videos, and even program files from a mobile device directly to the Next-Generation Control on a Haas CNC machine. Available for Android and iOS devices.

Included