

---

# ST-20Y

## Travels

X Axis \_\_\_\_\_

Y Axis \_\_\_\_\_

Z Axis \_\_\_\_\_

## Options

Visual Part Programming System \_\_\_\_\_

4000-rpm Spindle \_\_\_\_\_

Standard Program Memory, 1 GB \_\_\_\_\_

User-Definable Macros \_\_\_\_\_

55-Gallon Coolant Tank \_\_\_\_\_

BMT65 Metric Standard Toolholder Kit \_\_\_\_\_

8.3" Hydraulic Chuck, A2-6 \_\_\_\_\_

Early Power-Failure Detection Module \_\_\_\_\_

Ethernet Interface \_\_\_\_\_

HaasConnect: Remote monitoring \_\_\_\_\_

HaasDrop \_\_\_\_\_

Media Display M-Code; M130 \_\_\_\_\_

Rigid Tapping \_\_\_\_\_

Spindle Orientation \_\_\_\_\_

1-Year Standard Warranty \_\_\_\_\_

Control Touch Screen \_\_\_\_\_

Variable Flow Coolant \_\_\_\_\_

WiFi Connection for the Haas Control \_\_\_\_\_

Metric Measurement Units \_\_\_\_\_

6000-rpm Speed Upgrade for Live Tooling \_\_\_\_\_

High-Pressure Coolant \_\_\_\_\_

Automatic Tool Presetter \_\_\_\_\_

CNC Control Cabinet Cooler \_\_\_\_\_

Belt-Type Chip Conveyor, Lathe \_\_\_\_\_

Programmable Hydraulic Tallstock \_\_\_\_\_

Auxiliary Coolant Filter \_\_\_\_\_

Driven Toolholder, 90 Degree, for BMT65 Turret × 2 \_\_\_\_\_

Driven Toolholder, Straight, for BMT65 Turret × 2 \_\_\_\_\_

Liner Guide Adapter Kit, 2.50" \_\_\_\_\_

Spindle Liner Kit, 2.50" max diameter \_\_\_\_\_